

[54] METHOD AND APPARATUS FOR REMOTE MONITORING OF VALVES AND VALVE OPERATORS

- [75] Inventors: Stanley N. Hale; Thomas Rak; Duane H. Rowicki, all of Cobb; Cain P. Ho, Fulton, all of Ga.
- [73] Assignee: Movats Incorporated, Marietta, Ga.
- [21] Appl. No.: 92,648
- [22] Filed: Sep. 3, 1987

Related U.S. Application Data

- [63] Continuation-in-part of Ser. No. 8:8 451, Apr. 4, 1986, Pat. No. 4,831,873.
- [51] Int. Cl.<sup>4</sup> ..... G10M 19/00
- [52] U.S. Cl. .... 73/168; 364/550
- [58] Field of Search ..... 73/168, 862.27, 862.28, 73/862.31, 862.32; 137/551; 324/127, 142, 158 MG; 318/729; 251/129.11, 129.12; 364/550, 551

References Cited

U.S. PATENT DOCUMENTS

- 4,029,122 6/1977 Jacques ..... 137/551
- 4,123,009 10/1978 Kilpinen ..... 241/30
- 4,321,529 3/1982 Simmonds et al. .... 324/83 R
- 4,333,118 6/1982 Comstedt et al. .... 361/30
- 4,542,649 9/1985 Charbonneau et al. .... 73/168
- 4,570,903 2/1986 Crass ..... 251/129.12

FOREIGN PATENT DOCUMENTS

- 431464 7/1975 U.S.S.R. .... 324/158 MG

OTHER PUBLICATIONS

Square D Company of Milwaukee, WI, Product Information Package Consisting of (a) Instruction Sheet for Class 8430 Type G Load Converter Relays, Nov. 83; (b) Bulletin M-629-Product Data-Sub.: Load Monitoring for Three Phase Induction Motors Using Class 8430 Type V Load Detector & Type G Converter, 1984; (c) Product News Control Products IC-27 Class 8430, Nov. 1983.

Advertisement by Movats Incorporated entitled "Verifying Motor Operated Valve Operability from Motor Control Center", Jul. 1986.

Primary Examiner—William A. Cuchlinski, Jr.  
 Assistant Examiner—W. Morris Worth  
 Attorney, Agent, or Firm—Louis T. Isaf

[57] ABSTRACT

A method and apparatus for providing a previously unattainable yet desirable function of monitoring, at a remote location and/or in a remote (non-intrusive) manner, the condition of a valve operator to signal a need for more thorough inspection and for possible maintenance of the valve or valve operator; the method and apparatus including the relating of output power (motor load) of the valve operator motor to the valve operator stem load, setting up a threshold value for the power parameter based on a maximum allowable operator thrust depletion; and periodically monitoring actual power parameter values at a remote location for comparison to the threshold value.

29 Claims, 13 Drawing Sheets

